

MCH5541

PNP/NPN Bipolar Transistor (-30V, (-)700mA, V_{CE(sat)} ; (-220)190mV (max)



ON Semiconductor®

www.onsemi.com

Overview

MCH5541 is (-)30V, (-)700mA, V_{CE(sat)} ; (-220)190mV (max), PNP/NPN 2 in 1 type MCPH5, Bipolar Transistor.


Features

- Composite type with a PNP / NPN transistor contained in one package, facilitating high-density mounting
- Ultrasmall package permitting applied sets to be small and slim.
Package : SC-88AFL / MCPH5 (2.0 × 1.6 × 0.85 mm)

Typical Applications

- MOSFET gate drivers
- Lamp drivers
- Relay drivers
- Motor drivers

Electrical Connection



- 1 : Base1
- 2 : Emitter Common
- 3 : Base2
- 4 : Collector2
- 5 : Collector1

Top view

ORDERING INFORMATION

See detailed ordering and shipping information on page 6 of this data sheet.

SPECIFICATIONS () : PNP

ABSOLUTE MAXIMUM RATINGS at Ta = 25°C (Note 1)

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	V _{CB0}		(-30) 40	V
Collector-to-Emitter Voltage	V _{CEO}		(-30) 30	V
Emitter-to Base Voltage	V _{EBO}		(-) 5	V
Collector Current	I _C		(-) 700	mA
Collector Current (Pulse)	I _{CP}	PW ≤ 10μs	(-) 3	A
Collector Dissipation	P _C	Mounted on a ceramic board (600mm ² x 0.8m)	0.5	W
Junction Temperature	T _j		150	°C
Storage Temperature	T _{stg}		-55 to +150	°C

Note 1 : Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

ELECTRICAL CHARACTERISTICS at Ta = 25°C (Note 2)

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	I _{CBO}	V _{CB} =(-)30V, I _E =0			(-) 100	nA
Emitter Cutoff Current	I _{EBO}	V _{EB} =(-)4V, I _C =0			(-) 100	nA
DC Current Gain	h _{FE}	V _{CE} =(-)2V, I _C =(-)50mA	(200) 300		(500) 800	
Gain-Bandwidth Product	f _T	V _{CE} =(-)2V, I _C =(-)50mA		(520) 540		MHz
Output Capacitance	C _{ob}	V _{CB} =(-)10V, f=1MHz		(4.7) 3.3		pF
Collector-to-Emitter Saturation Voltage	V _{CE(sat)}	I _C =(-)200mA, I _B =(-)10mA		(-110) 85	(-220) 190	mV
Base-to-Emitter Saturation Voltage	V _{BE(sat)}	I _C =(-)200mA, I _B =(-)10mA		(-) 0.9	(-) 1.2	V
Collector-to-Base Breakdown Voltage	V _{(BR)CBO}	I _C =(-)10μA, I _E =0	(-30) 40			V
Collector-to-Emitter Breakdown Voltage	V _{(BR)CEO}	I _C =(-)1mA, R _{BE} =∞	(-) 30			V
Emitter-to-Base Breakdown Voltage	V _{(BR)EBO}	I _E =(-)10μA, I _C =0	(-) 5			V

Continued on next page.


MCH5541

Continued from preceding page.



Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Turn-ON Time	t_{on}	See specified Test Circuit.		35		ns
Storage Time	t_{stg}	See specified Test Circuit.		(125) 255		ns
Fall Time	t_f	See specified Test Circuit.		(25) 40		ns

Note 2 : Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.









Switching Time Test Circuit











$20I_{B1} = -20I_{B2} = I_C = 300\text{mA}$
 For PNP, minus sign is omitted.





MCH5541



MCH5541



MCH5541




PACKAGE DIMENSIONS

unit : mm

SC-88AFL / MCPH5

CASE 419AP

ISSUE O



MCH5541

ORDERING INFORMATION

Device	Marking	Package	Shipping (Qty / Packing)
MCH5541-TL-E	E1	SC-88AFL / MCPH5 (Pb-Free)	3000 / Tape & Reel

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D. http://www.onsemi.com/pub_link/Collateral/BRD8011-D.PDF

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.