

NSG1002MX

Product Preview RF SP3T Switch MMIC

This device is single pole triple throw (SP3T) type RF antenna switch MMIC. It has low insertion loss and high isolation. This is designed for wireless communication applications such as WLAN.

It adopts a small surface mount package and it is also suitable for portable devices such as smart phones.

Features

- Low Insertion Loss
- High Isolation
- Middle Power
- Small-sized Package
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

Typical Applications

- IEEE802.11 a/b/g/n/ac WLAN, Bluetooth® Systems
- LTE
- Wireless Communication Applications

MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Control Voltage	V _{CTL}	6	V
Power Dissipation	P _D	150	mW
Storage Temperature Range	T _{stg}	-55 to +150	°C
Operating Temperature Range	T _{opr}	-40 to +105	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

TRUTH TABLE

On Path	V _{CTL1}	V _{CTL2}	V _{CTL3}
IN – OUT1	High	Low	Low
IN – OUT2	Low	High	Low
IN – OUT3	Low	Low	High




ON Semiconductor®

www.onsemi.com



DFN8
MX SUFFIX
CASE 716AE

ELECTRICAL CONNECTION



MARKING DIAGRAM



AA = Specific Device Code
M = Month Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
NSG1002MXT1G	DFN8 (Pb-Free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

This document contains information on a product under development. ON Semiconductor reserves the right to change or discontinue this product without notice.

NSG1002MX


ELECTRICAL CHARACTERISTICS at Ta = 25°C (Note 1) Control Voltage : 0 / +3.0 V, DC Blocking capacitor 10.0 pF

Parameter	Symbol	Path	Condition	Value			Unit
				Min	Typ	Max	
Insertion Loss	IL	IN to OUT1, OUT2, OUT3	f = 2.5 GHz		0.45	0.65	dB
			f = 6.0 GHz		0.65	0.95	
Isolation	ISL	IN to OUT1, OUT2, OUT3	f = 2.5 GHz	23.0	28.0		dB
			f = 6.0 GHz	20.0	25.0		
Return Loss	RL		f = 2.5 GHz		30.0		dB
			f = 6.0 GHz		17.0		
1 dB Loss Compression Input Power	Pin 1 dB	IN to OUT1, OUT2, OUT3	f = 2.5 GHz		30.0		dBm
			f = 6.0 GHz		30.0		
Switching Control Current	I _{CTL}		No Signal		0.1		μA

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. Pay attention to handling since it is liable to be affected by static electricity due to the high-frequency process adopted.



Test Circuit



NSG1002MX

PACKAGE DIMENSIONS

X2DFN8 1.6x1.6, 0.4P
CASE 716AE
ISSUE O




NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.10 AND 0.20 mm FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

DIM	MILLIMETERS		
	MIN	NOM	MAX
A	0.30	0.35	0.40
A1	---	---	0.05
A3	0.125 REF		
b	0.13	0.18	0.23
D	1.50	1.60	1.70
D2	1.11	1.16	1.21
E	1.50	1.60	1.90
E2	0.64	0.69	0.74
e	0.40 BSC		
K	0.20 REF		
L	0.15	0.25	0.35

RECOMMENDED SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

Bluetooth is a registered trademark of Bluetooth SIG.

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marketing.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative